HP EliteDisplay E243d 23.8-inch Docking Monitor



Touch down to an instant workspace

Make the most of your desk with streamlined USB-C[™]¹, network, and accessory connectivity, plus a pop-up HD webcam, with the HP EliteDisplay E243d 23.8-inch Docking Monitor, our most advanced 23.8" docking display.



Maximum efficiency in a modern, minimalist footprint

• Create a command center from a display and built-in docking station that's ready to drive your workspace as soon as you plug in. Power your notebook and send and receive video over driverless USB-C™.¹ Connect your wired network through the RJ-45.

Control your window to the world

Reveal more of your work and support virtually seamless tiling with a 60.45 cm (23.8") diagonal IPS FHD screen and 3-sided micro-edge bezel. Daisy chain a second display² from one PC connection with a DisplayPort™ output.

Expand your view

- Experience a virtually seamless dual-display setup with 3-sided micro-edge bezels when you daisy chain a second display from a single USB-C™ connection on your PC.⁵
- Save time by leaving your USB devices connected to one of the 4 USB 3.0 ports, and access your network through the RJ-45. Maintain legacy compatibility with VGA, HDMI, and DisplayPort™ out ports.
- Work comfortably with adjustable tilt, height, and swivel settings. Use pivot rotation to conveniently customize portrait or landscape views.
- Do even more with an easy clean desk solution. Attach your HP EliteDesk Mini Desktop PC directly behind the display and power it through the USB-C™ connection.
- Design the screen for how you work with HP Display Assistant software, which enables screen partitioning and helps deter theft by dimming a display that's disconnected without approval.
- Rest assured that your IT investment is supported by a three-year standard limited warranty.

HP EliteDisplay E243d 23.8-inch Docking Monitor Specifications Table







| Display type | IPS with LED backlight |
|------------------------------|--|
| Display size (diagonal) | 60.45 cm (23.8") |
| Viewing angle | 178° horizontal; 178° vertical |
| Brightness | 250 cd/m ²¹ |
| Contrast ratio | 1000:1 static; 5000000:1 dynamic ¹ |
| Response Ratio | 7 ms gray to gray ¹ |
| Product colour | Asteroid bezel and Jack black stand |
| Aspect ratio | 16:09 ¹ |
| Native resolution | FHD (1920 x 1080 @ 60 Hz) |
| Resolutions supported | 1280 x 1024; 1280 x 720; 1280 x 768; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400; 800 x 600 |
| Display features | Anti-glare; Anti-static; BrightView panel; In plane switching; Language selection; LED backlights; Low haze; Onscreen controls; Pivot rotation; Plug and Play; User programmable |
| User controls | Brightness; Color control; Contrast; Exit; Image control; Information; Input source; Language; Management; Menu; Power; USB host selection |
| Input signal | 1 HDMI 1.4; 1 VGA; 1 USB Type-C [™] (Alternative mode DisplayPort [™] 1.2, power delivery up to 65 W); 1 USB Type-B ^{4,5} (with HDCP support for USB-C [™] and HDMI) |
| Ports and Connectors | 1 audio-in; 1 headphone-out; 1 RJ-45; 1 USB 3.1 (fast charging, power delivery up to 7.5 W); 3 USB 3.1 (power delivery up to 4.5 W); 1 DisplayPort™ 1.2-out ^{1,5} |
| Camera | 720p integrated HD with dual array microphone and LED |
| Environmental | Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing |
| Power | Input voltage 100 to 240 VAC |
| Power consumption | 155 W (maximum), 38 W (typical), 0.5 W (standby) |
| Dimensions | 53.88 x 4.535 x 32.19 cm (Without stand.) |
| Weight | 6.2 kg (With stand.) |
| Ergonomic features | Swivel: ±45°; Tilt: -5 to +23°; Pivot rotation: 90° |
| Physical security features | Security lock-ready ³ |
| Certification and compliance | Australian-New Zealand MEPS; BSMI; BSMI AS/NZS 3548 Class B; CB; CCC; CE; cTUVus; EAC; FCC; ICES; ISO 9241-307; KC; KCC; Microsoft WHQL Certification (Windows 10, Windows 8.1 and Windows 7); NOM; PSB; SmartWay Transport Partnership (NA); TUV-S; UL; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; China Energy Label (CEL) Grade 3 |
| Environmental specifications | Arsenic-free display glass; Low halogen; Mercury-free display backlights ² |
| What's in the box | AC power cord; Documentation; HDMI cable; USB Type-C™ cable; USB Type-A to B cable; DC-DC cable; DC jack dongle; External power supplier; QSP; Product notice |

HP EliteDisplay E243d 23.8-inch Docking Monitor

Accessories and services (not included)

HP B300 PC Mounting Bracket



Customize an altogether better solution with the HP B300 PC Mounting Bracket, which lets you attach your HP Workstation, HP Desktop Mini, HP Chromebox or select HP Thin Client directly behind select 2017 and 2018 HP EliteDisplays and HP Z Displays. ¹ Customize an altogether better solution with the HP B300 PC Mounting Bracket, which lets you attach your HP Workstation, HP Desktop Mini, HP Chromebox or select HP Thin Client directly behind select 2017 and 2018 HP EliteDisplays and HP Z Displays. ¹ Product number: 2016/304

Product number: 2DW53AA

HP S100 Speaker Bar



Add rich stereo audio to select 2017 and 2018 HP ProDisplays, HP EliteDisplays, and HP Z Displays without crowding your desk with the HP S100 Speaker Bar, which fits neatly underneath the display head and connects through USB. Add rich stereo audio to select 2017 and 2018 HP ProDisplays, HP EliteDisplays, and HP Z Displays without crowding your desk with the HP S100 Speaker Bar, which fits neatly underneath the display head and connects through USB. through USB

Product number: 2LC49AA

HP DisplayPort Cable Kit



Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor. Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor.

Product number: VN567AA

HP 5 year Next business day Onsite Standard Monitor Hardware Support



Receive 5 years of next business day onsite HW Support from an HP-qualified technician for your computing device, if the issue cannot be solved remotely. **Product number: U7935E**

HP EliteDisplay E243d 23.8-inch Docking Monitor

Messaging Footnotes

- 1 Video over USB-C™ requires a PC with USB-C™ DisplayPort™ Alt mode or Thunderbolt™. Power delivery over USB-C™ up to 65 Watts. Refer to Power Output in product QuickSpecs for exact specifications, PC must be compatible with the display's power output
- ² Additional displays sold separately
- 3 Internet access required and sold separately
- ⁵ Additional display sold separately. Source PC must have a USB-C™ or USB-A connection PC connection to the display through USB-C™ is only supported up to 65 Watts power delivery. USB-A connection requires source PC to support DisplayLink. Not compatible over DisplayPort™, VGA or HDMI connections.
- 6 HP EliteDesk Mini Desktop PC, sold separately. must have a USB-C™ port. Requires HP B300 PC Mounting Bracket for Monitors, sold separately.
- ⁷ Power up to 65 Watts through USB-C™

Technical Specifications Footnotes

- ¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower ² External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

- 3 Lock is sold separately.

 4 1 USB Type-C™ with HDCP support.

 5 Only one host PC should be connected to either USB Type-C™ port or DC OUT port for Power pass through. Connecting two Host PCs to the HP EliteDisplay E243d 23.8-inch Docking Monitor may result in system shutdown, loss of power, and the need to power-cycle the monitor's AC supply

Sign up for updates hp.com/go/getupdated

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

